

# GRANUSIL<sup>®</sup> Mineral Fillers

*By Unimin Corporation*

---

## PRODUCT SUBMITTAL

- Technical Data
- MSDS Sheet



GHP Systems, Inc.  
1000 32<sup>nd</sup> Avenue  
Brookings, SD 57006  
[www.ghpsystems.com](http://www.ghpsystems.com)

(605) 697-7867 tel  
(605) 697- 9118 fax  
888-447-7757 toll-free

## FEATURES AND BENEFITS

OTTAWA, MN

GRANUSIL<sup>®</sup> Mineral Fillers are produced from high purity industrial quartz sands for a wide variety of industrial and contractor mixed applications which need a reliable silica contribution or require a chemically inert structural filler. Consistently uniform grain shapes and particle size distributions offer excellent placement, compaction and mechanical properties. High silica content combined with low level soluble ions, alkalis and alkaline oxides provide non-reactive service in most corrosive and exposed environments.

These durable monocrystalline structures resist abrasion in high traffic-excessive wear applications and provide the stability formulators seek in high solids emulsions, elastomeric, cemented and modified cementitious systems. GRANUSIL<sup>®</sup> is the preferred structural component in systems ranging from polymerized floor overlays to artificial sports turf.

All GRANUSIL<sup>®</sup> grades are processed and sized under rigid SPC and UNIMIN QIP<sup>SM</sup> statistical and quality assurance programs. The result is chemical purity and consistently uniform particle size distributions for predictable performance in either manufactured or site-prepared products.

## PARTICLE SIZE ANALYSIS AND PROPERTIES

Mean Values. These Do Not Represent A Specification.

	Mesh	4095	4075	4060	4030	4020	5020	5010	7020
	ASTM E-11								
Typical Mean %	16	---	---	---	---	---	---	---	---
Retained on	20	1.2	0.4	0.3	---	---	---	---	---
Individual	30	36.1	29.0	11.4	0.1	---	---	---	---
Sieves	40	57.2	55.5	40.2	22.5	18.1	2.4	0.4	0.1
	50	5.1	12.0	30.6	54.7	35.8	19.9	12.2	1.2
	70	---	---	10.1	17.4	29.1	37.2	30.9	24.1
	100	---	---	---	4.2	12.4	26.5	32.8	42.7
	140	---	---	---	0.9	3.8	11.0	17.7	23.5
	200	---	---	---	---	0.8	2.7	5.3	7.2
	270	---	---	---	---	---	0.3	0.7	1.1
	PAN	0.4	3.1	7.4	0.2	---	---	---	0.1

Grain Shape	Rounded	Visual
Hardness	7.0 Mohs	Mohs Scale
Moisture Content	<0.1%	ASTM C-566
Specific Gravity	2.65 g/cm <sup>3</sup>	ASTM C-128
Bulk Density, aerated	92-95 lb/ft <sup>3</sup>	ASTM C-29
Bulk Density, compacted	98-100 lb/ft <sup>3</sup>	ASTM C-29

**CHEMICAL ANALYSIS**

Mean Values. These Do Not Represent A Specification.

**Mean Percent by Weight**

Silicon Dioxide (SiO <sub>2</sub> )	99.692
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	.038
Aluminum Oxide (Al <sub>2</sub> O <sub>3</sub> )	.073
Calcium Oxide (CaO)	.014
Titanium Dioxide (TiO <sub>2</sub> )	.006
Magnesium Oxide (MgO)	.012
Potassium Oxide (K <sub>2</sub> O)	.020
Sodium Oxide (Na <sub>2</sub> O)	.005
Loss on Ignition (LOI)	.121

**ORDERING INFORMATION**

**Shipping Point:** OTTAWA, MN  
ORIGINATING CARRIER: UNION PACIFIC (UP)

**Availability:** BULK, 50# AND 100# PAPER BAGS, AND IBC'S  
TRUCK AND RAIL

**UNIMIN**

UNIMIN CORPORATION

**FOR PRODUCT INFORMATION AND CUSTOMER SERVICE:**

U.S. and CANADA 800-243-9004 · FAX 800-243-9005

WORLDWIDE 203-966-1306 · FAX 203-972-1378

Silica Sands · Ground Silica · Feldspar · Ball Clay · Kaolin · Nepheline Syenite · High Purity Quartz · Olivine · Microcrystalline Silica · Bentonite Clay · Dolomite

GRADE NUMBERS INDICATE RELATIVE VALUES OR RESULTS. THEY ARE NOT A SPECIFICATION OR WARRANTY OF PERFORMANCE.

**HEALTH HAZARD WARNING:** Prolonged inhalation of dust associated with the materials described in this data sheet can cause delayed lung injury including Silicosis, a progressive, disabling and sometimes fatal lung disease. IARC has determined that crystalline silica, inhaled from occupational sources, can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure. Follow OSHA or other relevant safety and health standards for the form of crystalline silica called Quartz. Current material safety data sheets, containing safety information, is available and should be consulted before usage.

Notice: While information contained herein is correct to the best of our knowledge, Unimin Corporation herein disclaims any warranties as to the accuracy of the same. Recommendations of suggestions are made without guarantee or representation as to result, since conditions of usage are beyond our control. All materials are sold to Unimin Corporation standards terms and conditions of sale and the conditions that buyer shall make his own tests to determine the suitability of such product for buyer's purpose. No statement contained herein shall be construed as a recommendation to infringe any patent.

Silica/Silica Containing  
GRANUSIL<sup>™</sup> is a trademark of UNIMIN Corporation or its subsidiaries. All rights reserved.

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/ UNDERTAKING**

**UNIMIN CORPORATION**  
 258 Elm Street  
 New Canaan, CT 06840

Emergency Telephone Number  
 (203) 966-8880

Telephone Number for Information  
 (203) 966-8880

**PRODUCT NAME:** Crystalline Silica in the form of Quartz – various grades

**SYNONYMS:** Quartz, Crystalline Silica, Silicon Dioxide

Date Prepared: May 2009

**SECTION 2: HAZARDS IDENTIFICATION**

This product is a chemically inert, non-combustible mineral.

**EMERGENCY OVERVIEW  
 WARNING!**

**Lung injury and cancer hazard. Do not breathe dust. May cause delayed lung injury. Long term exposure can cause silicosis. Silicosis is a respiratory disease, which can result in delayed, disabling and sometimes fatal lung injury. IARC and NTP have determined that crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure. A single exposure will not result in serious adverse effects. See "Health Hazards" in Section 11 for detailed information. See exposure limit presentation in Section 8 for further information.**

Avoid creating dust when handling, using or storing. Use only with adequate ventilation to keep exposure below recommended exposure limits.

EU Classification of Substance/Preparation: Harmful (Xn) R48/20

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

CAS# / EINECS #	Component	Percentage	EU Classification (67/548/EEC)
14808-60-7 / 238-878-4	Crystalline Silica in the form of Quartz	87 - 99.9%	Xn R48/20

Refer to section 16 for further information on EU Classification.

See Section 8 for occupational exposure limit information

**SECTION 4: FIRST AID MEASURES**

**Gross Inhalation:** Remove victim to fresh air. If breathing has stopped, perform artificial respiration. If breathing is difficult have qualified personnel administer oxygen. Get prompt medical attention.

**Skin Contact:** No first aid should be needed since dermal contact with this product does not affect the skin. Wash exposed skin with soap and water before breaks and at the end of the shift.

**Eye Contact:** Flush the eyes immediately with large amounts of running water, lifting the upper and lower lids occasionally. If irritation persists or for imbedded foreign body, get immediate medical attention.

**Ingestion:** If large amounts are swallowed, get immediate medical attention.

## SECTION 5: FIREFIGHTING MEASURES

**Extinguishing Media:** This product will not burn but is compatible with all extinguishing media. Use any media that is appropriate for the surrounding fire.

**Special Fire Fighting Procedures:** None required with respect to this product. Firefighters should always wear self-contained breathing apparatus for fires indoors or in confined areas.

**Unusual Fire and Explosion Hazards:** None.

**Hazardous Combustion Products:** None.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

Wear appropriate protective equipment. If uncontaminated, collect using dustless method (HEPA vacuum or wet method) and place in appropriate container for use. If contaminated: a) use appropriate method for the nature of contamination, and b) consider possible toxic or fire hazards associated with the contaminating substances. Collect for appropriate disposal.

## SECTION 7: HANDLING AND STORAGE

**Do not breathe dust. Do not rely on your sight to determine if dust is in the air. Silica may be in the air without a visible dust cloud.** Use normal precautions against bag breakage or spills of bulk material. Avoid creation of respirable dust. Do not use as a dry abrasive blasting agent. ANSI/AIHA Z9.4:1997 recommends that silica sand be prohibited as an abrasive blasting agent for use in fixed location abrasive-blast enclosures. Use good housekeeping in storage and use areas to prevent accumulation of dust in work area.

To reduce the risk of developing silicosis, lung cancer and other adverse health effects, the ACGIH recommends that the industrial hygienist use every means available to keep exposures below the recommended TLV. NIOSH recommends reducing airborne exposure levels as low as possible below NIOSH's recommended exposure limit, substituting less hazardous materials when feasible, using appropriate respiratory protection when source controls cannot keep exposures below the recommended limit and making medical examinations available to exposed workers.

Use adequate ventilation and dust collection. To minimize exposure, wear a respirator approved for silica dust when using, handling, storing or disposing of this product or bag. Refer to the most recent standards of ANSI (Z88.2), OSHA (29 CFR 1910.134), MSHA (30 CFR Parts 56 and 57) and NIOSH Respirator Decision Logic. Maintain, clean and fit test respirators in accordance with OSHA regulations. Maintain and test ventilation and dust collection equipment. Launder clothing that has become dusty. Empty containers (bags, bulk containers, storage tanks, etc.) retain silica residue and must be handled in accordance with the provisions of this Material Safety Data Sheet. **WARN and TRAIN** employees in accordance with state and federal regulations.

**WARN YOUR EMPLOYEES (AND YOUR CUSTOMERS AND USERS IN CASE OF RESALE) BY POSTING, AND OTHER MEANS, OF THE HAZARDS AND OSHA AND ANY OTHER APPLICABLE REGULATORY PRECAUTIONS TO BE USED. PROVIDE TRAINING FOR YOUR EMPLOYEES ABOUT OSHA PRECAUTIONS.**

See also American Society for Testing and Materials (ASTM) Standard Practice E1132-99a, "Standard Practice for Health Requirements Relating to Occupational Exposure to Respirable Crystalline Silica".

Additional information on silica hazards and precautionary measures can be found at the following websites:

NIOSH Joint Campaign on Silicosis Prevention <http://www.cdc.gov/niosh/topics/silica/#campaign>

OSHA Crystalline Silica Website <http://www.osha.gov/SLTC/silicacrystalline/index.html>

MSHA Silicosis Prevention Website <http://www.msha.gov/S&HINFO/SILICO/SILICO.HTM>

NIOSH Hazard Review – Health Effects of Occupational Exposure to Respirable Crystalline Silica Website <http://www.cdc.gov/niosh/docs/2002-129/02-129a.html>

<b>SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION</b>
---

Exposure LimitsDefinitions:

MSHA means Mine Safety and Health Administration.

NIOSH means National Institute for Occupational Safety and Health.

OSHA means Occupational Safety and Health Administration.

PEL means OSHA Permissible Exposure Limit.

REL means the NIOSH Recommended Exposure Limit.

TLV means American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value.

TWA means time-weighted average.

OSHA PEL and MSHA Exposure Limit for Crystalline Silica, Quartz	$\frac{10 \text{ mg/m}^3}{\% \text{ Silica} + 2}$
(Respirable measured as an 8-hour TWA)	

TLV- 0.025 mg/m<sup>3</sup> 8-hour TWA (respirable fraction)

In 2006 the ACGIH lowered the TLV for Silica, Crystalline:  $\alpha$ -Quartz and Cristobalite to 0.025 mg/m<sup>3</sup> stating in the *Documentation of the TLV* "Because the time between exposure and signs of fibrosis is characteristically very long, as much as 30 to 40 years, the margin of safety for exposure to crystalline silica at the proposed TLV-TWA is not known precisely. Given the observed association between silicosis and lung cancer, it is recommended that air concentrations be maintained as far below the proposed TLV as prudent practices permit. The recommended TLV-TWA of 0.025 mg/m<sup>3</sup>, respirable particulate mass, is intended to prevent pulmonary fibrosis that may be a risk factor for lung cancer. An A2, Suspected Human Carcinogen, notation is based on the demonstrated association between lung cancer and the presence of silicosis." The documentation further states "A lack of toxicological and industrial hygiene data does not permit the recommendation of a TLV-STEL. However, it should be noted that high exposures of short duration to freshly fragmented crystalline particles do produce an acute and rapidly progressive form of silicosis. The reader is encouraged to review the section on *Excursion Limits* in the "Introduction to the Chemical Substances" of the current TLVs<sup>®</sup> and BEIs<sup>®</sup> book for guidance and control of excursions above the TLV-TWA, even when the 8-hour TWA is within the recommended limits"

NIOSH has issued its REL of 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m<sup>3</sup>) as determined by a full shift sample up to 10-hour working day, 40 hours per week. NIOSH has recommended that OSHA and MSHA adopt the NIOSH REL as the OSHA PEL and the MSHA Exposure Limit. The 1974 NIOSH Criteria for a Recommended Standard for Occupational Exposure to Crystalline Silica should be consulted for more detailed information. Additionally, NIOSH, in a publication entitled NIOSH Hazard Review Health Effects of Occupational Exposure to Respirable Silica (April 2002), NIOSH stated "...that workers have a significant risk of developing chronic silicosis when they are exposed to respirable crystalline silica over a working lifetime at the current Occupational Safety and Health Administration (OSHA) permissible exposure limit (PEL), the Mine Safety and Health Administration (MSHA) PEL, or the National Institute for Occupational Safety and Health (NIOSH) recommended exposure limit (REL). ...Current sampling and analytical methods used to evaluate occupational exposure to respirable crystalline silica do not meet the accuracy criterion needed to quantify exposures at concentrations below the NIOSH REL of 0.05 mg/m<sup>3</sup> as a time-weighted average (TWA) for up to a 10-hr workday during a 40-hr workweek. Until improved sampling and analytical methods are developed for respirable crystalline silica, NIOSH will continue to recommend an exposure limit of 0.05 mg/m<sup>3</sup> to reduce the risk of developing silicosis, lung cancer, and other adverse health effects. NIOSH also recommends minimizing the risk of illness that remains for workers exposed at the REL by substituting less hazardous materials for crystalline silica when feasible, by using appropriate respiratory protection when source controls cannot keep exposures below the NIOSH REL, and by making medical examinations available to exposed workers."

Crystalline silica exists in several forms, the most common of which are quartz (i.e. this product), trydimite and cristobalite, with quartz being the most common form found in nature. If quartz is heated to more than 870°C, it can change form to trydimite and if quartz is heated to more than 1450°C, it can change form to cristobalite. The OSHA PELs and MSHA Exposure Limits for trydimite and cristobalite are one-half of the PEL for quartz.

**Ventilation:** Use local exhaust as required to maintain exposures as far as possible below applicable occupational exposure limits. See also ACGIH "Industrial Ventilation - A Manual for Recommended Practice" (current edition). Control of exposure to dust must be accomplished as far as feasible by accepted engineering control measures (for example, enclosure or confinement of the operation, general or local exhaust ventilation and substitution of less toxic materials).

**Respiratory Protection:** When effective engineering controls are not feasible, or while they are being implemented, appropriate respiratory protection must be used. Use appropriate respiratory protection for respirable particulates based on consideration of airborne workplace concentrations and duration of exposure arising from intended end use. Refer to the most recent standards of ANSI (Z88.2), OSHA (29 CFR 1910.134), MSHA (30 CFR Parts 56 and 57) and NIOSH Respirator Decision Logic.

**Gloves:** Protective gloves recommended.

**Eye Protection:** Safety glasses or goggles recommended.

**Other Protective Equipment/Clothing:** As appropriate for the work environment. Dusty clothing should be laundered before reuse.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Appearance and Odor:** White powder, odorless.

**pH:** Not applicable

**Boiling Point:** 4046°F / 2230°C

**Melting Point:** 2930°F / 1610°C

**Solubility in Water:** Negligible

**Percent Volatile:** 0%

**Autoignition Temp:** Will not burn

**Specific Gravity (water=1):** 2.65

**Vapor Pressure:** Not applicable

**Vapor Density:** Not applicable

**Evaporation Rate:** Not applicable

**Flash Point (Method Used):** Fully oxidized, will not burn

**Flammable Limits: LEL:** Not applicable

**UEL:** Not applicable

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable

**Conditions to Avoid:** None

**Incompatibility:** Powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, etc.

**Hazardous Decomposition Products:** Silica will dissolve in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride.

**Hazardous Polymerization:** Will not occur.

**Conditions to Avoid:** None

## SECTION 11: TOXICOLOGICAL INFORMATION

### HEALTH HAZARDS:

**Inhalation:** Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may have the following serious chronic health effects:

**Silicosis:** Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling and sometimes fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop mycobacterial infections (tuberculous and non-tuberculous) and fungal infections. Inhalation of air with a very high concentration of respirable silica dust can cause the most serious forms of silicosis in a matter of

months or a few years. Some epidemiologic studies have concluded that there is significant risk of developing silicosis even at airborne exposure levels that are equal to the recommended NIOSH REL, the ACGIH TLV, the OSHA PEL, and the MSHA Exposure Limit.

**Cancer Status:** The International Agency for Research on Cancer has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1 - carcinogenic to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (published in June 1997) in conjunction with the use of these materials. The National Toxicology Program classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the Eleventh Report on Carcinogens (2005). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

**Other Data with Possible Relevance to Human Health:**

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) rheumatoid arthritis, systemic lupus, erythematosis, sarcoidosis, chronic bronchitis, chronic obstructive pulmonary disease (COPD), emphysema, chronic kidney disease and end-stage renal disease.

For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume 155, pages 761-768, 1997, and see also NIOSH Hazard Review – Health Effects of Occupational Exposure to Respirable Crystalline Silica, April 2002 (see Section 7 for NIOSH Hazard Review Website).

**Skin Contact:** No adverse effects expected.

**Eye Contact:** Contact may cause mechanical irritation and possible injury.

**Ingestion:** No adverse effects expected for normal, incidental ingestion.

**Chronic Health Effects:** See "Inhalation" subsection above with respect to silicosis, cancer status and other data with possible relevance to human health.

**Medical Conditions Aggravated by Exposure:** Individuals with respiratory disease, including but not limited to asthma and bronchitis, or subject to eye irritation, should not be exposed to respirable quartz dust.

**Signs and Symptoms of Exposure:** Exposure to dust may cause mucous membrane and respiratory irritation, cough, sore throat, nasal congestion, sneezing and shortness of breath. However, there may be no immediate signs or symptoms of exposure to hazardous concentrations of respirable crystalline silica (quartz). See "Inhalation" subsection above for symptoms of silicosis. The absence of symptoms is not necessarily indicative of safe conditions.

**Acute Toxicity Values:** Silica: LD50 oral rat >22,500 mg/kg.

## SECTION 12: ECOLOGICAL INFORMATION

Silica: LC50 carp >10,000 mg/L/72 hr. This product is not expected to present an environmental hazard.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Silica is not classified as a hazardous waste under US EPA RCRA regulations. If uncontaminated, dispose as an inert, non-metallic mineral. If contaminated, dispose in accordance with all applicable local, state/provincial and federal regulations in light of the contamination present. Local regulations may be more stringent than regional and

national requirements. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

#### SECTION 14: TRANSPORT INFORMATION

##### U.S. DOT HAZARD CLASSIFICATION

Proper Shipping Name: Not Regulated

Technical Name: N/A

UN Number: N/A

Hazard Class/Packing Group: N/A

Labels Required: None

DOT Packaging Requirements: N/A

Exceptions: N/A

#### SECTION 15: REGULATORY INFORMATION

SARA 311/312: Hazard Categories for SARA Section 311/312 Reporting: Chronic Health

SARA 313 This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under the SARA Section 313 (40 CFR 372): None

CERCLA Section 103 Reportable Quantity: None

California Proposition 65: This product contains crystalline silica (respirable) which is known to the State of California to cause cancer.

Toxic Substances Control Act: All of the components of this product are listed on the EPA TSCA Inventory or exempt from premanufacture notification requirements.

European Inventory of Commercial Chemical Substances: All of the components of this product are listed on the EINECS Inventory or exempt from notification requirements. (The EINECS number for Quartz: 238-878-4)

European Community Labeling: Harmful Xn

Contains crystalline silica, quartz (238-878-4)

R48/20 Harmful: Danger of serious damage to health by prolonged exposure by inhalation.

S22 Do not breathe dust

S38 In case of insufficient ventilation, wear suitable respiratory equipment.

Canadian Environmental Protection Act: All the components of this product are listed on the Canadian Domestic Substances List or exempt from notification requirements.

Canadian WHMIS Classification: Class D, Division 2, Subdivision A (Very Toxic Material causing other Toxic Effects)

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

Japan METI: All of the components of this product are existing chemical substances as defined in the Chemical Substance Control Law.

Australian Inventory of Chemical Substances: All of the components of this product are listed on the AICS inventory or exempt from notification requirements.

Australian National Occupational Health & Safety Commission Status: Hazardous according to the criteria of Australian National Occupational Health & Safety Commission -Harmful (Xn) R48/20 Harmful: Danger of serious damage to health by prolonged exposure by inhalation.

Korea: All of the components of this product are listed on the ECL inventory or exempt from notification requirements.

Philippines: All of the components of this product are listed on the PICCS inventory or exempt from notification requirements.

## 16: OTHER INFORMATION

### EU Classes and Risk Phrases for Reference (See Sections 2 and 3)

Xn Harmful

R48/20 Harmful: Danger of serious damage to health by prolonged exposure by inhalation.

S22 Do not breathe dust

S38 In case of insufficient ventilation, wear suitable respiratory equipment.

NFPA Hazard Rating: Health: 1 Fire: 0 Reactivity: 0

HMIS Hazard Rating: Health: \* Fire: 0 Reactivity: 0

\* Warning - Chronic health effect possible - inhalation of silica dust may cause lung injury/disease (silicosis). Take appropriate measures to avoid breathing dust. See Section 3.

### References:

Registry for Toxic Effects of Chemical Substances (RTECS), 2006

Patty's Industrial Hygiene and Toxicology

NIOSH Hazard Review – Health Effects of Occupational Exposure to Respirable Crystalline Silica, April 2002

NTP Eleventh Report on Carcinogens, 2005

IARC Monograph Volume 68, Silica, Some Silicates and Organic Fibres, 1997

Hazardous Substances Data Bank (HSDB), 2006

Documentation of the TLV – Silica, Crystalline:  $\alpha$ -Quartz and Cristobalite, American Conference of Governmental Industrial Hygienists, 2006

Revision Summary: Switched Sections 2 and 3. Updated websites in Section 7.

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data the Unimin Corporation believes reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside the control of Unimin Corporation, no warranties, expressed or implied, are made and no liability is assumed in connection with any use of this information. Any use of these data and information must be determined by the user to be in accordance with federal, state and local laws and regulations.