

FEATURES AND BENEFITS

OTTAWA, MN

GRANUSIL[®] Mineral Fillers are produced from high purity industrial quartz sands for a wide variety of industrial and contractor mixed applications which need a reliable silica contribution or require a chemically inert structural filler. Consistently uniform grain shapes and particle size distributions offer excellent placement, compaction and mechanical properties. High silica content combined with low level soluble ions, alkalis and alkaline oxides provide non-reactive service in most corrosive and exposed environments.

These durable monocrystalline structures resist abrasion in high traffic-excessive wear applications and provide the stability formulators seek in high solids emulsions, elastomeric, cemented and modified cementitious systems. GRANUSIL[®] is the preferred structural component in systems ranging from polymerized floor overlays to artificial sports turf.

All GRANUSIL[®] grades are processed and sized under rigid SPC and UNIMIN QIPSM statistical and quality assurance programs. The result is chemical purity and consistently uniform particle size distributions for predictable performance in either manufactured or site-prepared products.

PARTICLE SIZE ANALYSIS AND PROPERTIES

Mean Values. These Do Not Represent A Specification.

	Mesh	4095	4075	4060	4030	4020	5020	5010	7020
	ASTM E-11								
	16	---	---	---	---	---	---	---	---
Typical Mean %	20	1.2	0.4	0.3	---	---	---	---	---
Retained on	30	36.1	29.0	11.4	0.1	---	---	---	---
Individual	40	57.2	55.5	40.2	22.5	18.1	2.4	0.4	0.1
Sieves	50	5.1	12.0	30.6	54.7	35.8	19.9	12.2	1.2
	70	---	---	10.1	17.4	29.1	37.2	30.9	24.1
	100	---	---	---	4.2	12.4	26.5	32.8	42.7
	140	---	---	---	0.9	3.8	11.0	17.7	23.5
	200	---	---	---	---	0.8	2.7	5.3	7.2
	270	---	---	---	---	---	0.3	0.7	1.1
	PAN	0.4	3.1	7.4	0.2	---	---	---	0.1

Grain Shape	Rounded	Visual
Hardness	7.0 Mohs	Mohs Scale
Moisture Content	<0.1%	ASTM C-566
Specific Gravity	2.65 g/cm ³	ASTM C-128
Bulk Density, aerated	92-95 lb/ft ³	ASTM C-29
Bulk Density, compacted	98-100 lb/ft ³	ASTM C-29

CHEMICAL ANALYSIS

Mean Values. These Do Not Represent A Specification.

Mean Percent by Weight

Silicon Dioxide (SiO ₂)	99.692
Iron Oxide (Fe ₂ O ₃)	.038
Aluminum Oxide (Al ₂ O ₃)	.073
Calcium Oxide (CaO)	.014
Titanium Dioxide (TiO ₂)	.006
Magnesium Oxide (MgO)	.012
Potassium Oxide (K ₂ O)	.020
Sodium Oxide (Na ₂ O)	.005
Loss on Ignition (LOI)	.121

ORDERING INFORMATION

Shipping Point: OTTAWA, MN
ORIGINATING CARRIER: UNION PACIFIC (UP)

Availability: BULK, 50# AND 100# PAPER BAGS, AND IBC'S
 TRUCK AND RAIL



UNIMIN CORPORATION

FOR PRODUCT INFORMATION AND CUSTOMER SERVICE:

U.S. and CANADA 800-243-9004 · FAX 800-243-9005

WORLDWIDE 203-966-1306 · FAX 203-972-1378

Silica Sands · Ground Silica · Feldspar · Ball Clay · Kaolin · Nepheline Syenite · High Purity Quartz · Olivine · Microcrystalline Silica · Bentonite Clay · Dolomite

GRADE NUMBERS INDICATE RELATIVE VALUES OR RESULTS. THEY ARE NOT A SPECIFICATION OR WARRANTY OF PERFORMANCE.

HEALTH HAZARD WARNING: Prolonged inhalation of dust associated with the materials described in this data sheet can cause delayed lung injury including Silicosis, a progressive, disabling and sometimes fatal lung disease. IARC has determined that crystalline silica, inhaled from occupational sources, can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure. Follow OSHA or other relevant safety and health standards for the form of crystalline silica called Quartz. Current material safety data sheets, containing safety information, is available and should be consulted before usage.

Notice: While information contained herein is correct to the best of our knowledge, Unimin Corporation herein disclaims any warranties as to the accuracy of the same. Recommendations of suggestions are made without guarantee or representation as to result, since conditions of usage are beyond our control. All materials are sold to Unimin Corporation standards terms and conditions of sale and the conditions that buyer shall make his own tests to determine the suitability of such product for buyer's purpose. No statement contained herein shall be construed as a recommendation to infringe any patent.

Silica/Silica Containing
 GRANUSIL™ is a trademark of UNIMIN Corporation or its subsidiaries. All rights reserved.